


LOW VOLTAGE LV XLPE BELL CABLES

1kV LV XLPE 4 Core Copper Armoured (1.5mm² to 16mm²)



Cable Description:



General Data:

Properties:

Copper 4 Core

Specification SANS 1507

Voltage Rating 600 / 1000V

PVC Insulated

Typical

Applications:

Underground Reticulation and

underground supply

Options:

Standard PVC

Red Stripe Blue Stripe



Technical Information and Photographs from CBI electric



LOW VOLTAGE LV XLPE BELL CABLES

1kV LV XLPE 4 Core Copper Armoured (1.5mm² to 16mm²)





Product Information:

Cable Size Approximate		Current			Voit Drop	Approximate Cable	
	Diameter		Rating		(Three Phase)	M	lass
(mm²)	(mm)	(A)		(mV/A/m)	(kg)		
		Ground	Duct	Air		Cable	Gross (500m)
1.5	15	30	25	25	25.08	0.44	220
2.5	16	39	33	33	15.36	0.51	255
4	17	51	43	45	9.56	0.61	305
6	18.5	64	54	57	6.38	0.74	370
10	20.5	86	73	79	3.79	0.96	480
16	23	110	94	105	2.39	1.25	625



Technical Information and Photographs from CBI electric

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400



Complete your Project:

Please select the items you require and we will be in touch

Cables and Wires: Lighting:

Indoor
Outdoor
General
Other
Other

Let an ACTOM Let an ACTOM

Specialist Contact you Specialist Contact you

Transformers (Distribution):

Indoor Indoor
Outdoor Outdoor
General General
Other Other

Accessories:

Let an ACTOM Let an ACTOM

Specialist Contact you Specialist Contact you

Specific Information:



For more Information on this Product Please Send us the Folowing

Product Information:	
Product Name:	
Quantity:	
Project Name:	
Date the Product is required:	
Your Contact Information:	
Name and Surname:	
Company:	
Email:	
Phone Number:	

Province:

Thank You

For having a Look at this Product

Please send this PDF back to us with all your Information



Scan the QR Code to visit our Website: