





2U Series

FEATURE


- Optimum configuration design for thermal diffusion, which can increase life expectancy prominently
- OPPLE HE electronic ballast inside, instant start and low temperature rise, providing a pleasant and safe working environment
- Wide voltage range circuit withstands frequent voltage fluctuation
- Up to 80% energy saving than standard incandescent bulbs, and 8000hours long life time

APPLICATION

- Hotel & office
- Shop & supermarket
- Various residential lighting



B22



E27



Model	Power (w)	Power Factor	Lumen (lm)	Efficacy (lm/w)	CCT (K)	D (mm)	L (mm)	Tube Diameter(mm)	Cap	Packing size (mm)	Qty/Ctn (pcs)	Life Time (hrs)
YPZ220/8-2U	8	0.6	370	46	6500	41	133	12	E27/B22	445*230*165	50	8000
YPZ220/8-2U	8	0.6	400	50	2700	41	133	12	E27/B22	445*230*165	50	8000
YPZ220/8-2U	8	0.6	370	46	6500	41	133	12	E27/B22	445*230*165	50	8000
YPZ220/8-2U	8	0.6	400	50	2700	41	133	12	E27/B22	445*230*165	50	8000
YPZ220/11-2U	11	0.6	600	55	6500	41	157	12	E27/B22	445*230*180	50	8000
YPZ220/11-2U	11	0.6	640	58	2700	41	157	12	E27/B22	445*230*180	50	8000
YPZ220/11-2U	11	0.6	600	55	6500	41	157	12	E27/B22	445*230*180	50	8000
YPZ220/11-2U	11	0.6	640	58	2700	41	157	12	E27/B22	445*230*180	50	8000
YPZ220/13-2U	13	0.6	700	54	6500	41	162	12	E27/B22	445*225*195	50	8000
YPZ220/13-2U	13	0.6	760	58	2700	41	162	12	E27/B22	445*225*195	50	8000
YPZ220/13-2U	13	0.6	700	54	6500	41	162	12	E27/B22	445*225*195	50	8000
YPZ220/13-2U	13	0.6	760	58	2700	41	162	12	E27/B22	445*225*195	50	8000
YPZ220/15-2U	15	0.6	740	49	6500	41	172	12	E27/B22	445*225*200	50	8000
YPZ220/15-2U	15	0.6	800	53	2700	41	172	12	E27/B22	445*225*200	50	8000
YPZ220/15-2U	15	0.6	740	49	6500	41	172	12	E27/B22	445*225*200	50	8000
YPZ220/15-2U	15	0.6	800	53	2700	41	172	12	E27/B22	445*225*200	50	8000



Simple replacement

