

### **BUILDING WIRES - SUBMERSIBLE PUMP**

## 3 & 4 Core Submersible PVC Flexible Pump Cable



### **Cable Description:**

Conductors: High conductivity bunched

flexible copper conductors

Insulated and General Purpose

Colour Coded: Waterproof Flexible PVC

Core: Insulated cores are Twisted

together and Filled with PVC

to give the cable a round

finish

**Sheath:** Tightly Bonded waterproof,

flexible PVC

Core Colours: 3 Core - Red, Yellow and

Blue

4 Core - Red, Yellow, Blue

and Black

#### **General Data:**

Properties:

Specification SABS 1574

Temperature Range -10°C to +80°C

Voltage Rating 600 / 1000V

Sheath Colours Blue for 3-core

Green for 4-core

Packaging \*500m Drum lengths

\*Cut lengths are also available on request \*Marked at one metre

intervals

Typical

**Applications:** 

Supplying Power Indoor, Outdoor, Mobile,

Portable, and fixed Pumping equipment

Cost Effective Boreholes, Drainage,

alternative for rubber Dewatering, cleaning and

insulated cables irrigation pump equipment

Used on Farms, in Mines, Dock-

yards, Municipalities, Construction Operations, Railways, Roadworks and

**Factories** 



Website: www.actomep.co.za

Technical Information and Photographs from Alvern Cables

Email: epsales.jhb@actom.com Tel: +27 11 878 3050



## **BUILDING WIRES - SUBMERSIBLE PUMP**

## 3 & 4 Core Submersible PVC Flexible Pump Cable



### **Product Information:**

Cable	Stranding	Nominal	mV Drop		600 / 1000W		Approximate
Size	No x Dia	Dia	Amp / mtr		<b>Cubicle Wiring Amp</b>		Cable Mass
					Rati	ngs	
(mm²)					(\		(kg / 100m)
			1ph 220V	3ph 380V	1ph 220V	3ph 380V	
1.5 (3 Core)	28 x 0.26	10.1	29	25	18	15	14.96
2.5 (3 Core)	44 x 0.26	11.1	18	15	24	21	19.30
4.0 (3 Core)	49 x 0.31	13.0	11	9.5	32	28	27.65
6.0 (3 Core)	74 x 0.31	14.7	7.3	6.4	41	36	37.82
10.0 (3 Core)	126 x 0.31	16.9	4.4	3.8	57	50	55.77
16.0 (3 Core)	200 x 0.31	18.9	2.8	2.4	76	68	76.38
1.5 (4 Core)	28 x 0.26	10.9	29	25	18	15	17.70
2.5 (4 Core)	44 x 0.26	12.0	18	15	24	21	23.12
4.0 (4 Core)	49 x 0.31	14.2	11	9.5	32	28	34.10
6.0 (4 Core)	72 x 0.31	16.0	7.3	6.4	41	36	46.0
10.0 (4 Core)	126 x 0.31	18.5	4.4	3.8	57	50	68.67
16.0 (4 Core)	200 x 0.31	20.7	2.8	2.4	76	68	94.87



**Technical Information and Photographs from Alvern Cables** 

Tel: +27 11 878 3050 Email: epsales.jhb@actom.com

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400



# **Complete your Project:**

## Please select the items you require and we will be in touch

Cables and Wires: Lighting:

Indoor
Outdoor
General
Other
Other

Let an ACTOM Let an ACTOM

Specialist Contact you Specialist Contact you

Transformers (Distribution):

Indoor Indoor
Outdoor Outdoor
General General
Other Other

**Accessories:** 

Let an ACTOM Let an ACTOM

Specialist Contact you Specialist Contact you

## **Specific Information:**

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400

Email: epsales.jhb@actom.com Tel: +27 11 878 3050 Website: www.actomep.co.za



## For more Information on this Product

# Please Send us the Folowing

<b>Product Information:</b>	
Product Name:	
Quantity:	
Project Name:	
Date the Product is required:	
Your Contact Information:	
Name and Surname:	
Company:	
Email:	
Phone Number:	

Province:

# **Thank You**

For having a Look at this Product

Please send this PDF back to us with all your Information



Scan the QR Code to visit our Website:

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400

Email: epsales.jhb@actom.com Tel: +27 11 878 3050 Website: www.actomep.co.za